



LED Bumper Upgrade Kit OP3R-ICKIT



Complete Plug and Play Kit
Proprietary IRIS Reflector Technology
693' of Usable Light from a 10 Watt LED

10 WATT LEDs	SPECIFICATIONS	
	WARRANTY	Extended
P PRIME PERFORMANCE	AVAILABLE HOUSING COLOR	Black
	AVAILABLE BEAM PATTERNS	10'
Multi-Volt ⚡ 9-32V DC INPUT	RAW LUMENS	1,720 lm
	EFFECTIVE LUMENS	1,204 lm
DC DIE-CAST HOUSING	WATTAGE	20
	WEIGHT	3.06 lb/1390 g
IP-68 EXTENDED WARRANTY	LED LIFESPAN	50,000 Hours
	IMAGES	
FRONT		SIDE
TECHNICAL DETAILS		
DIMENSIONS		3.74" x 3.79" x 3.74" ea
OPTIC PURITY		95 mm x 96.5 mm x 95 mm ea
DRIVEN AT		90%
INPUT VOLTAGE		90%
AMP DRAW (12V)		9-32V DC
IP RATING		1.67A
VIBRATION RATING		IP-68
OPERATING TEMP		15.6 G
ADDED FEATURES		-40 Celsius ~ +85 Celsius
<ul style="list-style-type: none"> • Weatherproof Deutsch Connector with Plug-and-Play Harness • Die-Cast Aluminum Housing • Polycarbonate Lens 		



OPTIMUS COMPARISON VS FACTORY

Halogen 55 Watt Low Beam Headlight

88 Feet

Halogen 55 Watt High Beam Headlight

153 Feet

Optimus Round LED Driving Light

693 Feet